

Pass4Leader

Pass4Leader

> Contact Us  Login / Register

-  HOME
-  ALL VENDORS
-  GUARANTEE
-  FAQ
-  TESTIMONIALS
-  CART (0)



Try **Online Engine** before you buy

We're not the only ones **excited** about Pass4Leader Practice Material ...

66966+ customers in 100+ countries use Pass4Leader Test Engine. Meet our customers.



<http://www.pass4leader.com/>

Latest Exam Guide & Learning Materials

Exam : 070-582

Title : Windows Embedded Standard 7 for Developers

Vendors : Microsoft

Version : DEMO

NO.1 You have a Windows Embedded Standard 7 image for a target device. The image includes Enhanced

Write Filter (EWF) along with the Hibernate Once Resume Many (HORM) package. You need to ensure

that you are able to modify the hibernate file.

What should you do first?

- A. Configure the EWF mode to the EWF RAM mode.
- B. Configure the EWF mode to the EWF RAM Reg mode.
- C. Use EWFMgr.exe to disable EWF and restart the device.
- D. Use EWFMgr.exe to deactivate HORM and restart the device.

Answer: D

NO.2 You are developing a Windows Embedded Standard 7 device. You have a custom application that

saves data to a specific folder named Folder1. You need to ensure that only Folder1 can be modified. What

should you do?

- A. Configure BitLocker.
- B. Configure File-Based Write Filter (FBWF) along with Folder1 as an exception.
- C. Configure Enhanced Write Filter (EWF) and manually commit the changes for Folder1.
- D. Configure Enhanced Write Filter (EWF) along with the Hibernate Once Resume Many (HORM) package.

Answer: B

NO.3 You are developing a Windows Embedded Standard 7 image for a headless device. The device is

connected to a corporate network. You need to access the command line of the device from a remote

computer. Which technology should you use?

- A. FTP Server
- B. Telnet Server
- C. Remote Access Service (RAS)
- D. Internet Information Server (IIS)

Answer: B

NO.4 You are developing a Windows Embedded Standard 7 image for a customer. Only applications signed

by the customer can be installed and executed on the device. You need to prevent the installation and execution of unauthorized applications on the device.

What should you do?

- A. Use BitLocker.
- B. Use AppLocker.
- C. Use Windows Defender.
- D. Use Windows Security Essential.

Answer: B

NO.5 You are developing a Windows Embedded Standard 7 image that will be deployed to 5,000 devices.

You have a third-party application. You need to ensure that the application is included in the image. What should you do?

- A. In Image Configuration Editor (ICE), add a synchronous command to install the application to the oobeSystem pass. Deploy the image to a master device. Capture the final image.
- B. In Image Configuration Editor (ICE), add a synchronous command to install the application to the auditUser pass. Deploy the image to a master device. Reseal and capture the final image.
- C. Deploy the image to a master device. Start the master device. Install the application in the master device. Capture the final image.
- D. Deploy the image to a master device. Run the master device in Audit mode. Install the application in the master device. Reseal and capture the final image.

Answer: D

NO.6 You are creating a Windows Embedded Standard 7 image for a target device. You use Image Configuration Editor (ICE) to configure the answer file. You need to ensure that when the device is turned on, user interaction is not required until the desktop appears. Which setting of EmbeddedEdition_x86 should you configure?

- A. AutoLogon
- B. DefaultConsent

- C. MachinePassword
- D. Distribution Share\Credentials

Answer: A

NO.7 You are developing a Windows Embedded Standard 7 image by using Image Configuration Editor (ICE).

You have an installation file for an application. You need to ensure that the application is deployed

automatically when the image is deployed. What should you do?

- A. Create a configuration set based on the answer file.
- B. Add the installation file shortcut to the Autostart folder.
- C. Add a value for the installation file to the HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Run registry key.
- D. Insert a synchronous command to the answer file to run the installation file.

Answer:D

NO.8 You are creating a Windows Embedded Standard 7 image for a target device. You use Image

Configuration Editor (ICE) to configure the

answer file for the image. You need to ensure that users will not be prompted for administrator credentials

by User Account Control (UAC)

on the device. What should you do?

- A. Insert a synchronous command during the WindowsPE pass.
- B. Configure the EnableLUA setting of EmbeddedEdition_x86 to False.
- C. Configure the MachinePassword setting of EmbeddedEdition_x86 by using the password of the administrator.
- D. Configure the Identification\Credentials settings of EmbeddedEdition_x86 by using the user name and password of the administrator.

Answer: B

NO.9 You are developing a Windows Embedded Standard 7 image. The target device has no display. You

deploy an application that displays custom dialog boxes. You need to configure the image to automatically

provide an answer to each custom dialog box. What should you do?

- A. Add and configure the Dialog Box Filter package.
- B. Configure the Windows Embedded Core component.
- C. Add and configure the Message Box Default Reply component.
- D. Add and configure the Shell Controls and UI Support Functions package.

Answer: A

NO.10 You are developing a Windows Embedded Standard 7 answer file for an image in Image Configuration

Editor

(ICE). Your image includes a third-party application. You need to add the application shortcut to the menu

list of most frequently used

programs. To which setting in ICE should you add the link information for Windows Embedded Core?

- A. Shell-Setup\TaskBarLinks
- B. Shell-Setup\StartPanelLinks
- C. Shell-Setup\ClientApplications
- D. Shell-Setup\OEMWelcomeCenterLinks

Answer: B